



EXPERIENCE TOGETHER

OVERALL DIMENSION

LED

LCD Display

Length X Width X Height 2114 X 830 X 1105 mm

Wheelbase 1415 mm

Seat Height 780 mm

Minimum Ground Clearance 150 mm Fuel Capacity 17 L

Curb Weight 206 kg

ELECTRIC

Meter

ENGINE

Engine Type

Displacement

Bore X Stroke

Power

Torque

Clutch Type

liquid-cooled, DOHC

Compression Ratio 11.1:1

CHASSIS

68.4 X 54.5 mm

32N·m / 7750rpm

2-cylinder inline, 4-stroke

29.5kw / 9500rpm

400 cc

Wet multi plate

MT3.5 X 17 MT4.5 X 17

Tire (Front)

Tire (Rear)

Suspension (Front)

Suspension (Rear)

120/70 ZR17 M/C CST

160/60 ZR17 M/C CST

Telescopic fork

Brake (Front)

Brake (Rear)

ABS&CBS

Mono suspension, side aligned

(adjustable preload and rebound)

Front and Rear Suspension Stroke 120 / 45

Double disc, J.JUAN double-piston caliper

Single disc, J.JUAN single-piston caliper ABS

ZHEJIANG CFMOTO POWER CO., LTD.



Copyright Zhejiang CFMOTO Power co., Ltd. 2016. All rights reserved. Vehicle specifications are subject to change without notice. Imagery may not reflect most current product specifications.

CFMOTO reserves the right to make improvements and/or design changes without any obligation to modify previously sold, assembled or fabricated equipment.



POSSIBILITIES

The naked styling of the 400NK is aesthetically pleasing and exudes a sporty demeanor. CFMOTO's attention to details is evident from the precisely sculpted sharp design of the 400NK.





At the heart of the 400NK is a powerful 400cc, twin-cylinder, inline engine which exhibits the power of 40HP @9500 RPM and torque of 32 NM @7750 RPM, which perfectly expresses the aggressiveness of a street-fighter. A thrilling machine that provides the best of both worlds: the two-map switch "Sport" and "Eco" can be a treat for any motorcycle enthusiast.

Hit the throttle, push the "Sport" mode, and the bike propels forward with eagerness in no time. Zooming past open roads leaves a wide grin on your face. The optimum performance of the motorcycle is when the engine opens up at 4500 RPM, revving sweetly through the six - speed gearbox towards a speed of about 140 kmph. Push it even further and the power builds progressively all the way to the higher rev range.

4 FUEL TANK

The 400NK comes as standard with a large 17 liter fuel tank for a long-lasting riding fun. The 17L fuel tank is beautifully shaped with muscular cuts that help the 400NK look wild and aggressive.

2 SHOCK ABSORBER

The front is equipped with a telescopic fork and the rear with cantilever monoshock with adjustable rebound at the rear greatly handles the bumps and provides a smooth ride.

3 MUFFLER

Twist the throttle and the engine fires up with a throaty acoustics from its four-cavity muffler.

5 BRAKE SYSTEM

Braking is spot-on. Stoppage duties are taken care by a 300mm twin disc at the front and 240mm single disc at the rear with Continental ABS system. Braking is a treat during occasional speed runs or panic stopping. It gives you confidence and motivates for enhanced riding experience with guaranteed safety.

